



Digital Displays

TABLETOP



Specifications

	32"	43"	55"
Display Type	32" TFT, LED Backlit	43" TFT, LED Backlit	55" TFT, LED Backlit
Display Resolution	3840 x 2160 (4k, Ultra-HD)	3840 x 2160 (4k, Ultra-HD)	3840 x 2160 (4k, Ultra-HD)
Aspect Ratio	16:09	16:09	16:09
Brightness	350 nit (cd/m ²)	500 nit (cd/m ²)	700 nit (cd/m ²)
Contrast	1100:01:00	1100:01:00	4000:01:00
Colors	1.06 Billion	1.06 Billion	1.06 Billion
Viewing Angle	178 degrees Horizontal and Vertical	178 degrees Horizontal and Vertical	178 degrees Horizontal and Vertical
Frame Rate	60Hz	60Hz	60Hz
Video Inputs	USB-C, HDMI	USB-C, HDMI	USB-C, HDMI
Touch Connection	USB-C, USB-B	USB-C, USB-B	USB-C, USB-B
Remote Commands	Connect via Ethernet	Connect via Ethernet	Connect via Ethernet
Touch Screen	PCAP, Finger & Stylus, palm rejection	PCAP, Finger & Stylus	PCAP, Palm Rejection, Finger & Stylus
Mounting	Tabletop stand approx 30 to 70 degree adjustment in 10 increments plus flat VESA 300 x 300mm / 200 x 200mm	Tabletop stand approx 30 to 70 degree adjustment in 10 increments plus flat VESA 400 x 400mm	Tabletop stand 45, 50, 55 degree adjustment plus flat VESA 400 x 400mm
Glass, Surface Treatment	3 mm Toughened, anti-glare	3 mm Toughened, anti-glare	3 mm Toughened, anti-glare
Audio	10W speakers	10W speakers	10W speakers
User Controls	OSD Buttons	OSD Buttons	OSD Buttons
	100 - 240VAC 50/60Hz /	100 - 240VAC 50/60Hz /	100 - 240VAC 50/60Hz /
Power Consumption	125 Watts	125 Watts	125 Watts
Dimensions	29"W x 17"H x 3"D	40"W x 23.8"H x 1.9"D	47.6"W x 26.8"H
Weight	25 lbs	35 lbs	Approx. 45 lbs
Shipping Dimensions	46"W x 10"H x 23"D	57"W x 36"H x 10"D	Approx. 57"W x 36"H x 10"D
Shipping Weight	34 lbs	45 lbs	Approx. 55 lbs



Scan to watch video & get more KIP Digital Displays info



www.KIP.com/digitaldisplays