



KIP COLOR MEDIA GUIDE

Media for KIP Color Systems





KIP COLOR MEDIA GUIDE

Product Reference

Bond Paper

Product No.	Size	Qty/Box
#8020 Digital Economy 20 lb. Bond		
802018500	18"x500'	2
802024500	24"x500'	2
802030500	30"x500'	2
802034500	34"x500'	2
802036500	36"x500'	2
#8024 Digital 24 lb. Premium Bond		
802424500	24"x500'	1
802430500	30"x500'	1
802436500	36"x500'	1
#80101 Digital 20 lb. Vellum		
8010136500	36"x500'	1
#8018 Translucent Bond		
801836500	36"x500'	2
Specialty Bond Paper		
Product No.	Size	Qty/Box
#8032 Digital 32 lb. Presentation Bond		
803224400	24"x400'	1
803230400	30"x400'	1
803236400	36"x400'	1
#8040 Heavy Weight 40 lb. Bond		
804024200	24"x200'	2
804030200	30"x200'	2
804036200	36"x200'	2
#80750 Indoor/Outdoor Waterproof Bond		
R1TR36500	36"x500'	1
#80903 Indoor/Outdoor Water Resistant 40 lb. Poster Paper		
8090336150	36"x150'	1
#80908 Blue Back 6 mil Poster Paper		
8090836200	36"x200'	1
#80906 Gloss 32 lb. Bond		
8090636300	36"x300'	1

Adhesive Media

Product No.	Size	Qty/Box
#8024RPA Adhesive Back Bond, 7.5 mil Repositionable		
8024RPA36164	36"x164'	1
#8024PSA Adhesive Back Bond, 7.5 mil Permanent		
8024PSA36164	36"x164'	1
#806CPSA Clear Film, Adhesive Back, 8 mil Permanent		
806CPSA	36"x100'	1
#806WPSA White Film, Adhesive Back, 7 mil Permanent		
806WPSA	36"x100'	1
#806WRPA White Film, Adhesive Back, 7 mil Low Tack		
806WRPA	36"x100'	1

Polyester Film

Product No.	Size	Qty/Box
#803CLR 3 mil Clear Film		
803CLR36150	36"x150'	1
#803X 3 mil Double Matte Film		
803X36150	36"x164'	1
#FILM4M 4 mil White Opaque Film		
FILM4M36165K	36"x165'	1

Banner Media

Product No.	Size	Qty/Box
#FUS75 Fusion Soft Polyester 7.5 mil Digital Synthetic Banner		
FUS7524200	24"x200'	1
FUS7536200	36"x200'	1
#FUS10 Fusion Soft Polyester 10 mil Digital Synthetic Banner		
FUS1024200	24"x200'	1
FUS1036200	36"x200'	1
#80855 Digital Textile 7 mil Banner		
8085536200	36"x200'	1

*Other sizes may be available, please inquire.



KIP COLOR MEDIA GUIDE

Media Specifications

Bond Paper		Weight	Finish	Opacity	Brightness	Core
8020	Digital Economy Bond	20 lb.	Matte	90 %	92	3"
8024	Digital Premium Bond	24 lb.	Matte	94 %	94	3"
80101	Digital Vellum - 20#	20 lb.	Matte	60 %	88	3"
8018	Translucent Bond	18 lb.	Matte	71 %	90	3"

Specialty Bond Paper		Weight	Finish	Opacity	Brightness	Core
8032	Presentation Bond	32 lb.	Matte	92 %	95	3"
8040	Heavy Weight Bond	40 lb.	Matte	94 %	96	3"
80750	Indoor/Outdoor Waterproof Bond	24 lb.	Matte	95 %	92	3"
80903	Indoor/Outdoor Water Resistant Poster Paper	40 lb.	Matte	95 %	81	3"
80908	Blue Back Poster Paper	6 mil	Satin	96 %	97	3"
80906	Gloss Bond - 32#	32 lb.	Gloss	94 %	94	3"

Adhesive Media		Weight	Finish	Opacity	Brightness	Core
8024RPA	Adhesive Back Bond – Repositionable	7.5 mil	Matte	94 %	94	3"
8024PSA	Adhesive Back Bond – Permanent	7.5 mil	Matte	94 %	94	3"
806CPSA	Clear Adhesive Film – Permanent	8 mil	Gloss	0 %	N/A	3"
806WPSA	Matte White Adhesive Film – Permanent	7 mil	Matte	96 %	94	3"
806WRPA	Matte White Adhesive Film – Low Tack	7 mil	Matte	96 %	94	3"

Polyester Film Media		Weight	Finish	Opacity	Brightness	Core
803CLR	3 mil Clear Film	3 mil	Gloss	0 %	N/A	3"
803X	3 mil Double Matte Film	3 mil	Matte	58 %	82	3"
FILM4M	4 mil White Opaque Film	4 mil	Satin	91 %	92	3"

Banner Media		Weight	Finish	Opacity	Brightness	Core
FUS75	Fusion Soft Polyester 7.5 mil Digital Synthetic Banner	7.5 mil	Matte	98 %	94	3"
FUS10	Fusion Soft Polyester 10 mil Digital Synthetic Banner	10 mil	Matte	98 %	94	3"
80855	Digital Textile Banner	7 mil	Satin	96 %	101	3"

Please Contact Your Company's Purchasing Department for Partner Purchase Price
Purchasing Department Staff please contact kc3@kipamerica.com for your cost



KIP America
KC3@kip.com
800.252.6793



KIP COLOR MEDIA GUIDE

Media Application Specifications

Product Categories	Item No.	Application Categories										Model			
		Architectural and Engineering (A/E/C)	Geographic Information System (GIS)	Posters and Presentations	Trade Shows and Event Displays	POP and Retail Displays	Outdoor Banner	Indoor Banner	Photo Enlargements	Education and Training	KIP 850 / 860 / 870 / 880 / 890	KIP 970 / 980 / 990	KIP 940 Print System	KIP 770	KIP 7170 / 7770 / 7970
Bond Paper															
Digital Economy Bond	8020	•	•							•	•	•	•	•	•
Digital Premium Bond	8024	•	•							•	•	•	•		•
Digital Vellum - 20#	80101	•	•							•	•	•	•	•	•
Digital Translucent Bond	8018	•	•							•	•	•	•	•	•

Specialty Bond Paper															
Presentation Bond	8032	•	•	•	•	•				•	•	•	•		
Heavy Weight Bond	8040			•	•	•		•	•	•	•	•	•		
Indoor/Outdoor Waterproof Bond	80750	•	•	•	•	•	•	•	•	•	•	•	•		•
Indoor/Outdoor Water Resistant Poster Paper	80903			•	•	•	•	•			•	•	•		
Blue Back Poster Paper	80908			•	•	•	•	•			•	•	•		
Gloss Bond - 32#	80906			•	•	•			•	•	•	•	•		

Adhesive Media															
Adhesive Back Bond – Repositionable	8024RPA			•	•	•				•	•	•	•		
Adhesive Back Bond – Permanent	8024PSA			•	•	•				•	•	•	•		
Clear Adhesive Film – Permanent	806CPSA			•	•	•					•		•		
Matte White Adhesive Film – Permanent	806WPSA			•	•	•					•		•		
Matte White Adhesive Film – Low Tack	806WRPA			•	•	•				•	•		•		

Polyester Film Media															
3 mil Clear Film	803CLR	•	•								•		•		
3 mil Double Matte Film	803X	•	•	•	•	•					•	•	•		•
4 mil White Opaque Film	FILM4M	•	•	•	•	•	•	•			•	•	•		

Banner Media															
Fusion Soft Polyester 7.5 mil Digital Synthetic Banner	FUS75			•	•	•	•	•		•	•	•	•		
Fusion Soft Polyester 10 mil Digital Synthetic Banner	FUS10			•	•	•	•	•		•	•	•	•		
Digital Textile Banner	80855	•	•	•	•	•	•	•	•	•	•	•			



KIP COLOR MEDIA GUIDE

Bond Media

Digital Economy Bond - 8020

Product Description	Digital Economy Bond is a cost-effective priced media ideal for general purpose copying and printing for low to medium coverage technical documents and for printing proofs of graphic images. Typical uses include AEC plan sets, color and monochrome check prints, office diagrams, charts and simple graphics or proofing prior to final printing on heavier media.	
Applications	Technical Applications: <ul style="list-style-type: none">• AEC Printing• Electrical Diagrams• Markups• Revision Notes	Business and Graphics Applications: <ul style="list-style-type: none">• Education and Training• Ad and Newspaper Proofing
Properties	Weight: <ul style="list-style-type: none">• 20 lb. / 75 gsm• 50 lb. Text Stock• 28 lb. Cover Stock• 4 pt Stock	Opacity: 90% Brightness: 92 Finish: Matte
Width & Length	18" x 500', 24" x 500', 30" x 500', 34" x 500', 36" x 500'	
Printer Conditions	Standard conditions apply: Temperature: 59 to 80F / 15 to 27C Relative Humidity: 20 – 70% RH	
Storage Conditions	Store media in the same Temperature and Humidity as the printer. Media should be acclimated to the printer environment for 48 hours prior to use. Repack open rolls when not in use.	
Printer Settings	Use the KIP Media Manager to select a compatible Media Name and corresponding Media Group based on the factory System Preset. This sets the correct Fuser Temperature, Transfer Voltages and Back up Data Settings for the specific media utilized at the correct Relative Humidity level. Media Name: Bond Media Group: Paper Economy (0) To customize the corresponding Media Name, use the Media Manager COPY function to duplicate and name as required.	
Notes:	<ul style="list-style-type: none">• Provides excellent toner adhesion but opacity and rag content can affect some solid colors.• Heavy toner coverage can cause curling of the media at the edges.	



KIP COLOR MEDIA GUIDE

Bond Media

Digital Premium Bond - 8024

Product Description	Digital Premium Bond is a bright white media for proposals and presentations. Typical uses include plan sets and draft prints. Heavier weight and brightness make this media ideal for reproducing high quality prints and lamination. Extra smooth surface improves toner adhesion and image resolution.	
Applications	Technical Applications: <ul style="list-style-type: none"> • Renderings • 3D Design • GIS Mapping • Geological Surveys 	Business and Graphics Applications: <ul style="list-style-type: none"> • Education and Training • Temporary Sales Signage
Properties	Weight: <ul style="list-style-type: none"> • 24 lb. / 90 gsm • 60 lb. Text Stock • 33 lb. Cover Stock • 5 pt Stock 	Opacity: 94% Brightness: 94 Finish: Matte
Width & Length	24" x 500', 30" x 500', 36" x 500'	
Printer Conditions	Standard conditions apply: Temperature: 59 to 80F / 15 to 27C Relative Humidity: 20 – 70% RH	
Storage Conditions	Store media in the same Temperature and Humidity as the printer. Media should be acclimated to the printer environment for 48 hours prior to use. Repack open rolls when not in use.	
Printer Settings	Use the KIP Media Manager to select a compatible Media Name and corresponding Media Group based on the factory System Preset. This sets the correct Fuser Temperature, Transfer Voltages and Back up Data Settings for the specific media utilized at the correct Relative Humidity level. Media Name: Standard Bond Media Group: Paper Standard (4) To customize the corresponding Media Name, use the Media Manager COPY function to duplicate and name as required.	
Notes:	<ul style="list-style-type: none"> • Heavy toner coverage can cause curling of the media at the edges. 	



KIP COLOR MEDIA GUIDE

Bond Media

Digital Vellum 20# - 80101

Product Description	Our 100% cotton fiber vellum is transparentized using a proprietary non-Volatile Organic Compounds process and has a bright-white finish for strong visual contrast. Thru-put vellum meets Federal Specifications UU-P-561H for Type IV and is archive ready.	
Applications	Technical Applications: <ul style="list-style-type: none"> • Renderings • 3D Design • GIS Mapping • Geological Surveys 	Business and Graphics Applications: <ul style="list-style-type: none"> • Education and Training • Temporary Sales Signage
Properties	Weight: 20 lb. / 75 gsm	Opacity: 60% Brightness: 88 Finish: Matte
Width & Length	36" x 500'	
Printer Conditions	Standard conditions apply: Temperature: 59 to 80F / 15 to 27C Relative Humidity: 20 – 70% RH	
Storage Conditions	Store media in the same Temperature and Humidity as the printer. Media should be acclimated to the printer environment for 48 hours prior to use. Repack open rolls when not in use.	
Printer Settings	Use the KIP Media Manager to select a compatible Media Name and corresponding Media Group based on the factory System Preset. This sets the correct Fuser Temperature, Transfer Voltages and Back up Data Settings for the specific media utilized at the correct Relative Humidity level. Media Name: Vellum Media Group: Tracing (1) To customize the corresponding Media Name, use the Media Manager COPY function to duplicate and name as required.	
Notes:	<ul style="list-style-type: none"> • Heavy toner coverage can cause curling of the media at the edges 	



KIP COLOR MEDIA GUIDE

Specialty Bond Media

Digital Translucent Bond - 8018

Product Description	Digital Translucent Bond is a cost-effective media ideal for general purpose copying and printing for low to medium coverage technical documents. Typical uses include color and monochrome check prints, or any documents that may require translucent properties.	
Applications	Technical Applications: <ul style="list-style-type: none">• AEC Printing• Electrical Diagrams• Markups• Revision Notes	Business and Graphics Applications: <ul style="list-style-type: none">• Education and Training• Ad and Newspaper Proofing
Properties	Weight: <ul style="list-style-type: none">• 18 lb. / 68 gsm	Opacity: 71% Brightness: 90 Finish: Matte
Width & Length	36" x 500'	
Printer Conditions	Standard conditions apply: Temperature: 59 to 80F / 15 to 27C Relative Humidity: 20 – 70% RH	
Storage Conditions	Store media in the same Temperature and Humidity as the printer. Media should be acclimated to the printer environment for 48 hours prior to use. Repack open rolls when not in use.	
Printer Settings	Use the KIP Media Manager to select a compatible Media Name and corresponding Media Group based on the factory System Preset. This sets the correct Fuser Temperature, Transfer Voltages and Back up Data Settings for the specific media utilized at the correct Relative Humidity level. Media Name: T-Bond Media Group: Paper Transparent (7) To customize the corresponding Media Name, use the Media Manager COPY function to duplicate and name as required.	
Notes:	<ul style="list-style-type: none">• Please check with the local KIP location in your country for availability• Provides excellent toner adhesion but opacity and wood pulp content can affect some solid colors.• Heavy toner coverage can cause curling of the media at the edges.	



KIP COLOR MEDIA GUIDE

Specialty Bond Media

Presentation Bond - 8032

Product Description	A superior quality bond that is bright white for strong visual contrast. The heavy weight of the product eliminates curling on heavy coverage images and reduces show through. Provides durable output capable of handling very heavy toner coverage. Use for high-end proposals, presentations and short-term signage. Exceptionally smooth surface provides improved toner adhesion for optimal results.	
Applications	Technical Applications: <ul style="list-style-type: none"> • Satellite Photo • GIS Mapping • CAD Cover Page • Road Maps 	Business and Graphics Applications: <ul style="list-style-type: none"> • Temporary Signage • Safety Poster • Grocery Store Signage • Variable Data Posters
	Display Graphics Applications: <ul style="list-style-type: none"> • Digital Photography • Retail Products 	Banner Applications: <ul style="list-style-type: none"> • Indoor Campaign Signage • Indoor Party Banner • Public Events
Properties	Weight: <ul style="list-style-type: none"> • 32 lb. / 120 gsm • 83 lb. Text Stock • 46 lb. Cover Stock • 6 pt Stock 	Opacity: 92% Brightness: 95 Finish: Matte
Width & Length	24" x 400', 30" x 400', 36" x 400'	
Printer Conditions	Special conditions apply: Temperature: 59 to 80F / 15 to 27C Relative Humidity: 40 – 70% RH • Printer Conditions must be strictly adhered to for this media. Relative Humidity below 40% may cause print quality issues.	
Storage Conditions	Store media in the same Temperature and Humidity as the printer. Media should be acclimated to the printer environment for 48 hours prior to use. Repack open rolls when not in use.	
Printer Settings	Use the KIP Media Manager to select a compatible Media Name and corresponding Media Group based on the factory System Preset. This sets the correct Fuser Temperature, Transfer Voltages and Back up Data Settings for the specific media utilized at the correct Relative Humidity level. Media Name: 32 lb. Presentation Bond Media Group: Paper Presentation (5) To customize the corresponding Media Name, use the Media Manager COPY function to duplicate and name as required.	
Notes:	You may experience print quality issues based on heavy toner coverage, environmental conditions and system maintenance.	



KIP COLOR MEDIA GUIDE

Specialty Bond Media

Heavy Weight Bond - 8040

Product Description	Heavy weight, high quality bond is bright white for strong contrast and manufactured to control curl and static. This bond is excellent for heavy coverage graphics, photographs and banners. Excellent versatility across a wide range of photo and display graphics applications. Good for long term applications such as signs and posters. The product is easy to mount and or laminate. Thick stock ensures no curling.	
Applications	Display Graphics Applications: <ul style="list-style-type: none"> • Digital photography • Point of Sale • Point of Purchase • Beverage/Food Industry 	Business and Graphics Applications: <ul style="list-style-type: none"> • Concert And Public Events • Safety Poster • Grocery Store Signage • Variable Data Posters
	Banner Applications: <ul style="list-style-type: none"> • Indoor Campaign Signage • Indoor Party Banner • Public Events 	
Properties	Weight: <ul style="list-style-type: none"> • 40 lb. / 150 gsm • 100 lb. Text Stock • 56 lb. Cover Stock • 7 pt Stock 	Opacity: 94% Brightness: 96 Finish: Matte
Width & Length	24" x 200', 30" x 200', 36" x 200'	
Printer Conditions	Special conditions apply: Temperature: 59 to 80F / 15 to 27C Relative Humidity: 40 – 70% RH • Printer Conditions must be strictly adhered to for this media. Relative Humidity below 40% may cause print quality issues.	
Storage Conditions	Store media in the same Temperature and Humidity as the printer. Media should be acclimated to the printer environment for 48 hours prior to use. Repack open rolls when not in use.	
Printer Settings	Use the KIP Media Manager to select a compatible Media Name and corresponding Media Group based on the factory System Preset. This sets the correct Fuser Temperature, Transfer Voltages and Back up Data Settings for the specific media utilized at the correct Relative Humidity level. Back Exit Setting Required. Media Name: Heavy Weight Bond Media Group: Paper Heavy (6) To customize the corresponding Media Name, use the Media Manager COPY function to duplicate and name as required.	
Notes:	<ul style="list-style-type: none"> • This weight of stock is the maximum capacity tested for this equipment. • You may experience print quality issues based on heavy toner coverage, environmental conditions and system maintenance. 	



KIP COLOR MEDIA GUIDE

Specialty Bond Media

Indoor/Outdoor Waterproof Bond (Rite in the Rain) - 80750

Product Description	This all-weather paper is a durable, recyclable paper that is acrylic coated to resist water. No laminating is necessary to protect valuable documents. The media is very popular with contractors, architects and engineers as their plans and specs can be protected from the elements that would normally destroy or damage any inkjet print. A light blue tint helps reduce outdoor glare and separates itself from other prints that cannot be exposed to water.	
Applications	Technical Applications: <ul style="list-style-type: none">• Satellite Photo• GIS Mapping• Technical Schematics• CAD Documents• Utility Documents• Road Maps	Business and Graphics Applications: <ul style="list-style-type: none">• Education• Training• Temporary Sales Signage• Variable Data Posters
Properties	Weight: <ul style="list-style-type: none">• 24 lb.	Opacity: 95% Brightness: 92 Finish: Matte
Width & Length	36" x 500'	
Printer Conditions	Standard conditions apply: Temperature: 59 to 80F / 15 to 27C Relative Humidity: 20 – 70% RH	
Storage Conditions	Store media in the same Temperature and Humidity as the printer. Media should be acclimated to the printer environment for 48 hours prior to use. Repack open rolls when not in use.	
Printer Settings	Use the KIP Media Manager to select a compatible Media Name and corresponding Media Group based on the factory System Preset. This sets the correct Fuser Temperature, Transfer Voltages and Back up Data Settings for the specific media utilized at the correct Relative Humidity level. Media Name: Waterproof Bond Media Group: Special 2 (9) To customize the corresponding Media Name, use the Media Manager COPY function to duplicate and name as required.	
Notes:	<ul style="list-style-type: none">• Please check with the local KIP location in your country for availability.• Additional shipping costs may be required and are the responsibility of the purchaser.	



KIP COLOR MEDIA GUIDE

Specialty Bond Media

Indoor/Outdoor Water Resistant Poster Paper - 80903

Product Description This is a one-sided coated paper that is latex-saturated which provides a wet-strength coating and offers exceptional print fidelity and a distinctive luster finish. Strength, flexibility and durability are hallmark traits to this media. The media resists cracking when folded and provides excellent waterproof signage.

Applications

<p>Display Graphics Applications:</p> <ul style="list-style-type: none"> • Information Boards • Point of Sale • Point of Purchase • Beverage/Food Industry 	<p>Business and Graphics Applications:</p> <ul style="list-style-type: none"> • Concert and Public Events • Safety Poster • Grocery Store Signage • Variable Data Posters • Training and Education
<p>Banner Applications:</p> <ul style="list-style-type: none"> • Indoor Campaign Signage • Indoor Party Banner • Public Events 	

Properties

<p>Weight:</p> <ul style="list-style-type: none"> • 40 lb. / 150 gsm • 100 lb. Text Stock • 56 lb. Cover Stock • 7 pt Stock 	<p>Opacity: 95%</p> <p>Brightness: 81</p> <p>Finish: Matte</p>
--	---

Width & Length 36" x 150'

Printer Conditions

Special conditions apply:
Temperature: 59 to 80F / 15 to 27C
Relative Humidity: 40 – 70% RH

- Printer Conditions must be strictly adhered to for this media. Relative Humidity below 40% may cause print quality issues

Storage Conditions Store media in the same Temperature and Humidity as the printer. Media should be acclimated to the printer environment for 48 hours prior to use. Repack open rolls when not in use.

Printer Settings Use the KIP Media Manager to select a compatible Media Name and corresponding Media Group based on the factory System Preset. This sets the correct Fuser Temperature, Transfer Voltages and Back up Data Settings for the specific media utilized at the correct Relative Humidity level. Back Exit Setting Required.

Media Name: Poster Paper
Media Group: Paper Special 1 (8)

To customize the corresponding Media Name, use the Media Manager COPY function to duplicate and name as required.

Notes:

- This weight of stock is the maximum capacity tested for this equipment.
- You may experience print quality issues based on heavy toner coverage, environmental conditions and system maintenance.
- Please check with the local KIP location in your country for availability.
- Additional shipping costs may be required and are the responsibility of the purchaser.



KIP COLOR MEDIA GUIDE

Specialty Bond Media

Blue Back Poster Paper - 80908

Product Description	Blue Back media features a waterproof backing to ensure no image bleed-through when installed over existing prints. The opacity is provided by the blue coating on the back of the media. Blue back can be used with secondary adhesives for low cost short term outdoor graphics on kiosks and billboards.	
Applications	Business and Graphics Applications: <ul style="list-style-type: none"> • Temporary Signage • Information Boards • Grocery Store Signage • Short-Term Bill Board Advertising 	Display Graphics Applications: <ul style="list-style-type: none"> • Digital Photography • Retail Products
Properties	Weight: <ul style="list-style-type: none"> • 6 mil 	Opacity: 96% Brightness: 97 Finish: Satin
Width & Length	36" x 200'	
Printer Conditions	Special conditions apply: Temperature: 59 to 80F / 15 to 27C Relative Humidity: 40 – 70% RH • Printer Conditions must be strictly adhered to for this media. Relative Humidity below 40% may cause print quality issues.	
Storage Conditions	Store media in the same Temperature and Humidity as the printer. Media should be acclimated to the printer environment for 48 hours prior to use. Repack open rolls when not in use.	
Printer Settings	Use the KIP Media Manager to select a compatible Media Name and corresponding Media Group based on the factory System Preset. This sets the correct Fuser Temperature, Transfer Voltages and Back up Data Settings for the specific media utilized at the correct Relative Humidity level. Media Name: Blue Back Paper Media Group: Paper Special 3 (10) To customize the corresponding Media Name, use the Media Manager COPY function to duplicate and name as required.	
Notes:	You may experience print quality issues based on heavy toner coverage, environmental conditions and system maintenance.	



KIP COLOR MEDIA GUIDE

Specialty Bond Media

Gloss 32# Bond - 80906

Product Description	A matte gloss media that helps to provide vivid, full color wide format prints. Due to the glossy finish, images “pop” and the gloss shines through light coverage areas. Appropriate for a wide range of commercial, point-of-purchase and point-of-sale applications. Immediately ready for mounting and laminating.	
Applications	Business and Graphics Applications: <ul style="list-style-type: none"> • Presentations • Education • Training • POP Signage 	Display Graphics Applications: <ul style="list-style-type: none"> • Digital Photography • Retail Products
Properties	Technical Applications: <ul style="list-style-type: none"> • CAD Cover Page 	Weight: <ul style="list-style-type: none"> • 32 lb. / 120 gsm • 83 lb. Text Stock • 46 lb. Cover Stock • 6 pt Stock
Width & Length	36” x 200’	
Printer Conditions	Special conditions apply: Temperature: 59 to 80F / 15 to 27C Relative Humidity: 40 – 70% RH <ul style="list-style-type: none"> • Printer Conditions must be strictly adhered to for this media. Relative Humidity below 40% may cause print quality issues. 	
Storage Conditions	Store media in the same Temperature and Humidity as the printer. Media should be acclimated to the printer environment for 48 hours prior to use. Repack open rolls when not in use.	
Printer Settings	Use the KIP Media Manager to select a compatible Media Name and corresponding Media Group based on the factory System Preset. This sets the correct Fuser Temperature, Transfer Voltages and Back up Data Settings for the specific media utilized at the correct Relative Humidity level. Media Name: Gloss Media Group: Gloss (3) To customize the corresponding Media Name, use the Media Manager COPY function to duplicate and name as required.	
Notes:	<ul style="list-style-type: none"> • You may experience print quality issues based on heavy toner coverage, environmental conditions and system maintenance. Please check with the local KIP location in your country for availability. • Print quality on Gloss media is affected by humidity and toner coverage can affect overall print quality. • Toner has a matte finish and will cover the gloss surface coating. Some users find that printing on 32 lb. / 120gsm media and laminating produces a better result. 	



KIP COLOR MEDIA GUIDE

Adhesive Backed Media

Adhesive Back Bond - Repositionable - 8024RPA

Product Description A bright white plain bond stock with an acrylic repositionable microsphere adhesive on the back side that will mount to a variety of surfaces. This product is an excellent choice for indoor signage. The thin silicone release liner removes easily for quick mounting.

Applications

Business and Graphics Applications:

- Presentations
- Education
- Indoor Signage
- POP Signage
- Retail Products
- Mount to board with no additional adhesive

Properties

Weight: 7.5 mil Total
Base Material: 24 lb. / 90 gsm Bond Paper
Liner: 2.4 mil Paper Liner
Temperature Range: 67F up to 77F (19C up to 25C)

Opacity: 94%
Brightness: 94
Finish: Matte

Width & Length 36" x 164'

Printer Conditions

Special conditions apply:
Temperature: 59 to 80F / 15 to 27C
Relative Humidity: 40 – 70% RH May require 0.35" lead edge margin Minimum cut length is 24"
 • Printer Conditions must be strictly adhered to for this media. Relative Humidity below 40% may cause print quality issues.

Storage Conditions Store media in the same Temperature and Humidity as the printer. Media should be acclimated to the printer environment for 48 hours prior to use. Repack open rolls when not in use.

Printer Settings Use the KIP Media Manager to select a compatible Media Name and corresponding Media Group based on the factory System Preset. This sets the correct Fuser Temperature, Transfer Voltages and Back up Data Settings for the specific media utilized at the correct Relative Humidity level. Back Exit Setting Required. For best color quality result, this specialty media may require a minimum cut length of 22"(560mm).

Media Name: Adhesive Bond Repositionable
Media Group: Adhesive Paper 1 (11)

To customize the corresponding Media Name, use the Media Manager COPY function to duplicate and name as required.

Notes:

- You may experience print quality issues based on heavy toner coverage, environmental conditions and system maintenance.
- Please check with the local KIP location in your country for availability.
- This media may deposit trace amounts of adhesive on the Cutter components and possibly within the paper path of the equipment. Additional service may be required.
- Cleaning of the paper path with an anti-static spray such as Brillianize may be necessary on a daily or weekly basis for high volume usage.
- Print stacking quantity is limited dependent on system configuration / model.
- Users should test the adhesive on the intended surface prior to usage.



KIP COLOR MEDIA GUIDE

Adhesive Backed Media

Adhesive Back Bond - Permanent - 8024PSA

Product Description	A bright white plain bond stock with an acrylic permanent microsphere adhesive on the back side that will mount to a variety of surfaces. This product is an excellent choice for indoor signage. The thin silicone release liner removes easily for quick mounting.	
Applications	Business and Graphics Applications: <ul style="list-style-type: none"> • Presentations • Education • Mount to board with no additional adhesive • POP Signage • Retail Products • Indoor Signage 	
Properties	Weight: 7.5 mil Total Base Material: 24 lb. / 90 gsm Bond Paper Liner: 2.4 mil Paper Liner Temperature Range: 41F up to 77F (5C up to 25C)	Opacity: 94% Brightness: 94 Finish: Gloss
Width & Length	36" x 164'	
Printer Conditions	Special conditions apply: Temperature: 59 to 80F / 15 to 27C Relative Humidity: 40 – 70% RH <ul style="list-style-type: none"> • Printer Conditions must be strictly adhered to for this media. Relative Humidity below 40% may cause print quality issues. 	
Storage Conditions	Store media in the same Temperature and Humidity as the printer. Media should be acclimated to the printer environment for 48 hours prior to use. Repack open rolls when not in use.	
Printer Settings	Use the KIP Media Manager to select a compatible Media Name and corresponding Media Group based on the factory System Preset. This sets the correct Fuser Temperature, Transfer Voltages and Back up Data Settings for the specific media utilized at the correct Relative Humidity level. Back Exit Setting Required. For best color quality result, this specialty media may require a minimum cut length of 22"(560mm). Media Name: Adhesive Bond Permanent Media Group: Adhesive Paper 2 (12) To customize the corresponding Media Name, use the Media Manager COPY function to duplicate and name as required.	
Notes:	<ul style="list-style-type: none"> • You may experience print quality issues based on heavy toner coverage, environmental conditions and system maintenance. • Please check with the local KIP location in your country for availability. • This media may deposit trace amounts of adhesive on the Cutter components and possibly within the paper path of the equipment. Additional service may be required. • Cleaning of the paper path with an anti-static spray such as Brillianize may be necessary on a daily or weekly basis for high volume usage. • Users should test the adhesive on the intended surface prior to usage. 	



KIP COLOR MEDIA GUIDE

Adhesive Backed Media

Clear Adhesive Film - Permanent - 806CPSA

Product Description	This product is a clear translucent polyester film with a paper backing that allows for printing for a variety of applications including see-thru window graphics, self-adhesive labels and signs on boards. Capable of sticking to a multitude of surfaces including plastic, glass metal or any other lacquered flat and smooth surface. KIP Clear Adhesive can be used outdoor without lamination. A 2 Mil polyester film is combined with a 4 Mil liner, total 6 Mil thickness.	
Applications	Business and Graphics Applications: <ul style="list-style-type: none"> • Window Graphics • Mount to board with no additional adhesive • Secondary Application: leave liner attached for high gloss graphic • Grocery Store Signage 	<ul style="list-style-type: none"> • POP Signage • Retail Products • Information Boards
Properties	Weight: 6 mil Total (49 lb. / 186 gsm) Base Material: 2 mil Polyester Clear Film Liner: 3.6 mil Paper Liner	Opacity: 0% Brightness: N/A Finish: Gloss
Width & Length	36" x 100'	
Printer Conditions	Special conditions apply: Temperature: 59 to 80F / 15 to 27C Relative Humidity: 40 – 55% RH <ul style="list-style-type: none"> • Printer Conditions must be strictly adhered to for this media. Relative Humidity below 40% may cause print quality issues. Stacking assistance may be necessary for images longer than 24" or with heavy coverage. KIP Auto Stacker may disabled to ensure stacking. 	
Storage Conditions	Store media in the same Temperature and Humidity as the printer. Media should be acclimated to the printer environment for 48 hours prior to use. Repack open rolls when not in use.	
Printer Settings	Use the KIP Media Manager to select a compatible Media Name and corresponding Media Group based on the factory System Preset. This sets the correct Fuser Temperature, Transfer Voltages and Back up Data Settings for the specific media utilized at the correct Relative Humidity level. Back Exit Setting Required. For best color quality result, this specialty media may require a minimum cut length of 22"(560mm). Media Name: Clear Adhesive Film Permanent Media Group: Adhesive Film 1 (13) To customize the corresponding Media Name, use the Media Manager COPY function to duplicate and name as required.	
Notes:	<ul style="list-style-type: none"> • Please check with the local KIP location in your country for availability. Additional shipping costs may be required and are the responsibility of the purchaser. • You may experience print quality issues based on heavy toner coverage, environmental conditions and system maintenance. • This media may deposit trace amounts of adhesive on the Cutter components and possibly within the paper path of the equipment. Additional service may be required. • Cleaning of the paper path with an anti-static spray such as Brillianize may be necessary on a daily or weekly basis for high volume usage. • Users should test the adhesive on the intended surface prior to usage. 	



KIP COLOR MEDIA GUIDE

Adhesive Backed Media

Matte White Adhesive Film - Permanent - 806WPSA

Product Description	KIP White Adhesive Film is a matte aqueous coated polyester film with a high grab, high-tack permanent pressure sensitive adhesive laminated to a 95 gsm paper release liner. The construction is optimized for dry toner print applications. This product allows for printing a variety of applications including window graphics, self-adhesive labels and signs on boards. Capable of sticking to a multitude of surfaces including plastic, glass, metal or any other flat and smooth surface. KIP Matte White Adhesive can be used for indoor or outdoor applications without lamination.	
Applications	<p>Business and Graphics Applications:</p> <ul style="list-style-type: none"> • Window Graphics • Mount to board with no additional adhesive • Grocery Store Signage • POP Signage • Retail Products • Information Boards 	
Properties	<p>Weight: 7 mil Total (51 lb. / 190 gsm) Base Material: 2 mil Polyester White Film Liner: 3.6 mil Paper Liner</p>	<p>Opacity: 96% Brightness: 94 Finish: Matte</p>
Width & Length	36" x 100'	
Printer Conditions	<p>Special conditions apply: Temperature: 59 to 80F / 15 to 27C Relative Humidity: 40 – 55% RH</p> <ul style="list-style-type: none"> • Printer Conditions must be strictly adhered to for this media. Relative Humidity below 40% may cause print quality issues. Stacking assistance may be necessary for images longer than 24" or with heavy coverage. 	
Storage Conditions	Store media in the same Temperature and Humidity as the printer. Media should be acclimated to the printer environment for 48 hours prior to use. Repack open rolls when not in use.	
Printer Settings	<p>Use the KIP Media Manager to select a compatible Media Name and corresponding Media Group based on the factory System Preset. This sets the correct Fuser Temperature, Transfer Voltages and Back up Data Settings for the specific media utilized at the correct Relative Humidity level. Back Exit Setting Required. For best color quality result, this specialty media may require a minimum cut length of 22"(560mm).</p> <p>Media Name: White Matte Adhesive Film Permanent Media Group: Adhesive Film 2 (14)</p> <p>To customize the corresponding Media Name, use the Media Manager COPY function to duplicate and name as required.</p>	
Notes:	<ul style="list-style-type: none"> • Please check with the local KIP location in your country for availability. Additional shipping costs may be required and are the responsibility of the purchaser. • You may experience print quality issues based on heavy toner coverage, environmental conditions and system maintenance. • This media may deposit trace amounts of adhesive on the Cutter components and possibly within the paper path of the equipment. Additional service may be required. • Cleaning of the paper path with an anti-static spray such as Brillianize may be necessary on a daily or weekly basis for high volume usage. • Users should test the adhesive on the intended surface prior to usage. 	



KIP COLOR MEDIA GUIDE

Adhesive Backed Media

Matte White Adhesive Film – Low Tack - 806WRPA

Product Description KIP White Adhesive Film is a matte aqueous coated polyester film with a low tack adhesive laminated to a 95 gsm paper release liner. The construction is optimized for dry toner print applications. This product allows for printing a variety of applications including window graphics, self-adhesive labels and signs on boards. Capable of sticking to a multitude of surfaces including plastic, glass, metal or any other flat and smooth surface. KIP Matte White Adhesive can be used for indoor or outdoor applications without lamination. Easily removable and repositionable.

Applications

Business and Graphics Applications:

- Window Graphics
- Mount to board with no additional adhesive
- Grocery Store Signage
- POP Signage
- Retail Products
- Information Boards

Properties

Weight: 7 mil Total (51 lb. / 190 gsm) **Opacity:** 96%
Base Material: 2 mil Polyester White Film **Brightness:** 94
Liner: 3.6 mil Paper Liner **Finish:** Matte

Width & Length 36" x 100'

Printer Conditions

Special conditions apply:
Temperature: 59 to 80F / 15 to 27C
Relative Humidity: 40 – 55% RH

- Printer Conditions must be strictly adhered to for this media. Relative Humidity below 40% may cause print quality issues. Stacking assistance may be necessary for images longer than 24" or with heavy coverage.

Storage Conditions Store media in the same Temperature and Humidity as the printer. Media should be acclimated to the printer environment for 48 hours prior to use. Repack open rolls when not in use.

Printer Settings Use the KIP Media Manager to select a compatible Media Name and corresponding Media Group based on the factory System Preset. This sets the correct Fuser Temperature, Transfer Voltages and Back up Data Settings for the specific media utilized at the correct Relative Humidity level. Back Exit Setting Required. For best color quality result, this specialty media may require a minimum cut length of 22"(560mm).

Media Name: White Matte Adhesive Film Low Tack
Media Group: Adhesive Film 3 (15)

To customize the corresponding Media Name, use the Media Manager COPY function to duplicate and name as required.

Notes:

- Please check with the local KIP location in your country for availability. Additional shipping costs may be required and are the responsibility of the purchaser.
- You may experience print quality issues based on heavy toner coverage, environmental conditions and system maintenance.
- This media may deposit trace amounts of adhesive on the Cutter components and possibly within the paper path of the equipment. Additional service may be required.
- Cleaning of the paper path with an anti-static spray such as Brillianize may be necessary on a daily or weekly basis for high volume usage.
- Users should test the adhesive on the intended surface prior to usage.



KIP COLOR MEDIA GUIDE

Polyester Film Media

3 mil Clear Film - 803CLR

Product Description	This high quality clear polyester film is flexible, water proof, strong, durable and 100% clear.	
Applications	Technical Applications: <ul style="list-style-type: none">• A/E/C Documents• CAD Overlays• GIS Mapping	
Properties	Weight: 3 mil / 116 gsm)	Opacity: 0% Brightness: N/A Finish: Gloss
Width & Length	36" x 150'	
Printer Conditions	Special conditions apply: Temperature: 50 to 86F / 10 to 30C Relative Humidity: 40 – 55% RH <ul style="list-style-type: none">• Printer Conditions must be strictly adhered to for this media. Relative Humidity below 40% may cause print quality issues. Stacking assistance may be necessary for images longer than 24" or with heavy coverage.	
Storage Conditions	Store media in the same Temperature and Humidity as the printer. Media should be acclimated to the printer environment for 48 hours prior to use. Repack open rolls when not in use.	
Printer Settings	Use the KIP Media Manager to select a compatible Media Name and corresponding Media Group based on the factory System Preset. This sets the correct Fuser Temperature, Transfer Voltages and Back up Data Settings for the specific media utilized at the correct Relative Humidity level. Back Exit Setting Required. For best color quality result, this specialty media may require a minimum cut length of 22"(560mm). Media Name: Clear Film 3.5 mil Media Group: Film Clear (16) To customize the corresponding Media Name, use the Media Manager COPY function to duplicate and name as required.	
Notes:	<ul style="list-style-type: none">• Please check with the local KIP location in your country for availability. Additional shipping costs may be required and are the responsibility of the purchaser.• You may experience print quality issues based on heavy toner coverage, environmental conditions and system maintenance.• Polyester Films generate large amounts of static, some lines may appear in continuous tone areas.• Print stacking quantity is limited dependent on system configuration / model.• Higher humidity environments will work best for this media.• Cleaning of the paper path with an anti-static spray such as Brillianize may be necessary on a daily or weekly basis for high volume usage.• Use of this media for graphics printing is not recommended due to the transparency of the toner on the clear film.	



KIP COLOR MEDIA GUIDE

Polyester Film Media

3 mil Double Matte Film - 803X

Product Description	This product is a 3 mil polyester film that is coated on both sides. While the media is traditionally used for long term storage of A/E/C documents, it can also be used for Backlit Signage by overlapping two copies. The product is dimensionally stable, durable, water resistant and tear resistant.	
Applications	Technical and Graphics Applications: <ul style="list-style-type: none">• A/E/C Documents – for long term storage	Display Graphics Applications: <ul style="list-style-type: none">• LED Backlit Signage• Fluorescent Backlit Signage
Properties	Weight: 3 mil / 116 gsm) Brightness: 96	Opacity: 58% Brightness: 82 Finish: Matte
Width & Length	36" x 164'	
Printer Conditions	Special conditions apply: Temperature: 59 to 80F / 15 to 27C Relative Humidity: 40 – 55% RH <ul style="list-style-type: none">• Printer Conditions must be strictly adhered to for this media. Relative Humidity below 40% may cause print quality issues. Stacking assistance may be necessary for images longer than 24" or with heavy coverage.	
Storage Conditions	Store media in the same Temperature and Humidity as the printer. Media should be acclimated to the printer environment for 48 hours prior to use. Repack open rolls when not in use.	
Printer Settings	Use the KIP Media Manager to select a compatible Media Name and corresponding Media Group based on the factory System Preset. This sets the correct Fuser Temperature, Transfer Voltages and Back up Data Settings for the specific media utilized at the correct Relative Humidity level. Front Stacking Limit is One Sheet of Matte Film. Back Exit Required for Multiple Sheets. For best color quality result, this specialty media may require a minimum cut length of 22"(560mm). Media Name: Matte Film Media Group: Film Matte (2) To customize the corresponding Media Name, use the Media Manager COPY function to duplicate and name as required.	
Notes:	<ul style="list-style-type: none">• Please check with the local KIP location in your country for availability. Additional shipping costs may be required and are the responsibility of the purchaser.• You may experience print quality issues based on heavy toner coverage, environmental conditions and system maintenance.• As Polyester Films generate large amounts of static, some lines may appear in continuous tone areas.• Higher humidity environments will work best for this media.• Cleaning of the paper path with an anti-static spray such as Brillianize may be necessary on a daily or weekly basis for high volume usage.	



KIP COLOR MEDIA GUIDE

Polyester Film Media

4 mil White Opaque Film - FILM4M

Product Description	Specialty film is heat stabilized polyester film with excellent toner adhesion. Designed for durability and great imaging. Superior tear resistance, requires no lamination. This media is capable of accepting banner tape and grommets to strengthen outdoor durability.	
Applications	Display Graphics Applications: <ul style="list-style-type: none"> • Indoor Banner • Outdoor Banner (with proper grommets and banner tape) • Grocery store signage • Campaign Events • Mount to board for waterproof sign 	Technical and Graphics Applications: <ul style="list-style-type: none"> • Weatherproof A/E/C Documents • GIS Mapping • Weather Mapping
Properties	Weight: 4 mil	Opacity: 91% Brightness: 92 Finish: Satin
Width & Length	36" x 165'	
Printer Conditions	Special conditions apply: Temperature: 59 to 80F / 15 to 27C Relative Humidity: 40 – 55% RH <ul style="list-style-type: none"> • Printer Conditions must be strictly adhered to for this media. Relative Humidity below 40% may cause print quality issues. Stacking assistance may be necessary for images longer than 24" or with heavy coverage. 	
Storage Conditions	Store media in the same Temperature and Humidity as the printer. Media should be acclimated to the printer environment for 48 hours prior to use. Repack open rolls when not in use.	
Printer Settings	<p>Use the KIP Media Manager to select a compatible Media Name and corresponding Media Group based on the factory System Preset. This sets the correct Fuser Temperature, Transfer Voltages and Back up Data Settings for the specific media utilized at the correct Relative Humidity level. Back Exit Setting Required. For best color quality result, this specialty media may require a minimum cut length of 22"(560mm).</p> <p>Media Name: White Opaque Film 4.5 mil Media Group: Film Opaque (17)</p> <p>To customize the corresponding Media Name, use the Media Manager COPY function to duplicate and name as required.</p>	
Notes:	<ul style="list-style-type: none"> • For outdoor longer term banner, we recommend that the outside 1" margin is seamed with double strength carpet/ banner tape. This allows for grommets to hold multiple layers of banner media, plus the banner tape. The banner tape also adds to the strength of banner. Wind reliefs should be applied as necessary. • Please check with the local KIP location in your country for availability. Additional shipping costs may be required and are the responsibility of the purchaser. • You may experience print quality issues based on heavy toner coverage, environmental conditions and system maintenance. • As Polyester Films generate large amounts of static, some lines may appear in continuous tone areas. Higher humidity environments will work best for this media. • Cleaning of the paper path with an anti-static spray such as Brillianize may be necessary on a daily or weekly basis for high volume usage. 	



KIP COLOR MEDIA GUIDE

Banner Media

Fusion Soft Polyester 7.5-Digital Synthetic Banner - FUS75

Product Description Fusion Soft Polyester 7.5 – Digital Synthetic Banner is an alternative to vinyl and Tyvek™ banner media. The media combines the characteristics of polyester and paper. The media is stain and tear resistant and waterproof, providing durability for both indoor and outdoor situations. Compared to other polyester materials, static build-up is not a problem which assures uninterrupted print runs. The product is stiff enough to use in banner stands without wrinkling during repeated use. Excellent use for hanging banners, X and roll-up banner stands

Applications

Display Graphics Applications:

- Indoor Banner
- Outdoor Banner (with proper grommets and banner tape)
- Grocery store signage
- X Banner stand
- Roll-up Banner stand
- Mount to board for waterproof sign
- Campaign Events

Properties

Caliper: 7.5 mil **Opacity:** 98% **Usage Temp:** 32F - 120F (OC - 49C)
Weight: 58 lb. / 210 gsm **Brightness:** 94
Finish: Matte

Width & Length 24" x 200', 36" x 200'

Printer Conditions

Special conditions apply:
Temperature: 59 to 80F / 15 to 27C
Relative Humidity: 40 – 55% RH

- Printer Conditions must be strictly adhered to for this media. Relative Humidity below 40% may cause print quality issues. Stacking assistance may be necessary for images longer than 24" or with heavy coverage.

Storage Conditions Store media in the same Temperature and Humidity as the printer. Media should be acclimated to the printer environment for 48 hours prior to use. Repack open rolls when not in use.

Printer Settings

Use the KIP Media Manager to select a compatible Media Name and corresponding Media Group based on the factory System Preset. This sets the correct Fuser Temperature, Transfer Voltages and Back up Data Settings for the specific media utilized at the correct Relative Humidity level. Back Exit Setting Required. For best color quality result, this specialty media may require a minimum cut length of 22"(560mm).

Media Name: Soft Poly 7.5 mil
Media Group: Special 1 (18)

To customize the corresponding Media Name, use the Media Manager COPY function to duplicate and name as required.

Notes:

- For outdoor longer term banner, we recommend that the outside 1" margin is seamed with double strength carpet/ banner tape. This allows for grommets to hold multiple layers of banner media, plus the banner tape. The banner tape also adds to the strength of banner. Wind reliefs should be applied as necessary.
- Please check with the local KIP location in your country for availability. Additional shipping costs may be required and are the responsibility of the purchaser.
- You may experience print quality issues based on heavy toner coverage, environmental conditions and system maintenance.
- Cleaning of the paper path with an anti-static spray such as Brillianize may be necessary on a daily or weekly basis for high volume usage.



KIP COLOR MEDIA GUIDE

Banner Media

Fusion Soft Polyester 10-Digital Synthetic Banner - FUS10

Product Description	Fusion Soft Polyester 10 – Digital Synthetic Banner is a robust alternative to vinyl and Tyvek™ banner media. This 10 mil version of the Fusion product combines the characteristics of polyester and paper and parallels the strength of many vinyl products. The media is almost 50% stronger than the Fusion 7.5 mil product. It is stain and tear resistant and waterproof, providing durability for both indoor and outdoor situations. Compared to other polyester materials, static build-up is not a problem which assures uninterrupted print runs. The product is stiff enough to use in banner stands without wrinkling during repeated use. Excellent use for hanging banners, X and roll-up banner stands		
Applications	Display Graphics Applications: <ul style="list-style-type: none"> • Indoor Banner • Outdoor Banner (with proper grommets and banner tape) • Grocery Store Signage • X Banner Stand • Roll-up Banner Stand • Mount to board for waterproof sign • Campaign Events 		
Properties	Caliper: 10 mil Weight: 75 lb. / 280 gsm	Opacity: 98% Brightness: 94 Finish: Matte	Usage Temp: 32F - 120F (OC - 49C)
Width & Length	24" x 200', 36" x 200'		
Printer Conditions	Special conditions apply: Temperature: 59 to 80F / 15 to 27C Relative Humidity: 40 – 55% RH <ul style="list-style-type: none"> • Printer Conditions must be strictly adhered to for this media. Relative Humidity below 40% may cause print quality issues. Stacking assistance may be necessary for images longer than 24" or with heavy coverage. 		
Storage Conditions	Store media in the same Temperature and Humidity as the printer. Media should be acclimated to the printer environment for 48 hours prior to use. Repack open rolls when not in use.		
Printer Settings	<p>Use the KIP Media Manager to select a compatible Media Name and corresponding Media Group based on the factory System Preset. This sets the correct Fuser Temperature, Transfer Voltages and Back up Data Settings for the specific media utilized at the correct Relative Humidity level. Back Exit Setting Required. For best color quality result, this specialty media may require a minimum cut length of 22"(560mm).</p> <p>Media Name: Soft Poly 10 mil Media Group: Special 2 (19)</p> <p>To customize the corresponding Media Name, use the Media Manager COPY function to duplicate and name as required.</p>		
Notes:	<ul style="list-style-type: none"> • For outdoor longer term banner, we recommend that the outside 1" margin is seamed with double strength carpet/ banner tape. This allows for grommets to hold multiple layers of banner media, plus the banner tape. The banner tape also adds to the strength of banner. Wind reliefs should be applied as necessary. • Please check with the local KIP location in your country for availability. Additional shipping costs may be required and are the responsibility of the purchaser. • You may experience print quality issues based on heavy toner coverage, environmental conditions and system maintenance. • Cleaning of the paper path with an anti-static spray such as Brillianize may be necessary on a daily or weekly basis for high volume usage. 		



KIP COLOR MEDIA GUIDE

Banner Media

Digital Textile Banner - 80855

Product Description	Digital Textile Banner is the perfect media for indoor long term or short term outdoor banners and technical documents. The wet strength, smooth surface and light gloss coating are perfect for soft POP signage or roll-up banner stands. Priced competitively with polypropylene, but with more strength and durability, the product is virtually tear-proof. This low cost solution is excellent for all of your banner needs yet inexpensive enough for weather-proof technical documents such as maps and aerial photographs.	
Applications	Display Graphics Applications <ul style="list-style-type: none"> • Indoor Banner • Outdoor Banner (with proper grommets and banner tape) • Roll-up Banner Stands • X Banner Stand • Mount to board for water proof sign 	Technical Applications <ul style="list-style-type: none"> • Weather proof A/E/C documents • GIS mapping
Properties	Weight: 7 mil / 140 gsm	Opacity: 96% Brightness: 101 Finish: Satin
Width & Length	36" x 200'	
Printer Conditions	Strict conditions apply: Temperature: 59 to 80F / 15 to 27C Relative Humidity: 40 – 55% RH <ul style="list-style-type: none"> • Printer Conditions must be strictly adhered to for this media. Relative Humidity below 40% may cause print quality issues. Stacking assistance may be necessary for images longer than 24" or with heavy coverage. 	
Storage Conditions	Store media in the same Temperature and Humidity as the printer. Media should be acclimated to the printer environment for 48 hours prior to use. Repack open rolls when not in use.	
Printer Settings	Use the KIP Media Manager to select a compatible Media Name and corresponding Media Group based on the factory System Preset. This sets the correct Fuser Temperature, Transfer Voltages and Back up Data Settings for the specific media utilized at the correct Relative Humidity level. Back Exit Setting Required. For best color quality result, this specialty media may require a minimum cut length of 22"(560mm). Media Name: Textile Banner 7 mil (SysK 2.x) or 7 mil Tritrex (SysK 1.x) Media Group: Special 3 (20) To customize the corresponding Media Name, use the Media Manager COPY function to duplicate and name as required.	
Notes:	<ul style="list-style-type: none"> • For outdoor longer term banner, we recommend that the outside 1" margin is seamed with double strength carpet/ banner tape. This allows for grommets to hold multiple layers of banner media, plus the banner tape. The banner tape also adds to the strength of banner. Wind reliefs should be applied as necessary. • Please check with the local KIP location in your country for availability. Additional shipping costs may be required and are the responsibility of the purchaser. • You may experience print quality issues based on heavy toner coverage, environmental conditions and system maintenance. • Cleaning of the paper path with an anti-static spray such as Brillianize may be necessary on a daily or weekly basis for high volume usage. 	



KIP

KC3@kip.com

800.252.6793